

## Farm Dump Trailers



7 Tonne Farm Dump Trailer



8 Tonne Farm Dump Trailer



8 Tonne Farm Dump Trailer



12 Tonne Farm Dump Trailer



14 Tonne Farm Dump Trailer

The AW Farm Dump Trailers are designed for use on the farm hauling materials such as manure and roots. They have a scow ended tapered body with a 5mm thick floor and 3mm thick sides supported by wide side channels. They have a strong wide parallel chassis built from RHS or PFC and are fitted with high specification running gear. The tandem axle models can be fitted with either sprung or bogie suspension. There are 6½ Tonne, 7 Tonne, 8 Tonne, 10 Tonne, 12 Tonne & 14 Tonne models available.

### Standard Farm Dump Trailer Features :-

- Hydraulic Tipping
- Hydraulic Brakes
- Commercial Ratchet type Park Brake
- Full Road Lighting
- Inspection Steps
- Rope Hooks
- Removable Drawbar Skid
- RHS Box Top on 10 Tonne model & above
- Heavy Duty Heat Treated Hitch Eye

### Optional Extras Available include :-

- Sprung Drawbar
- Manual Tailboard
- Hydraulic Tailboard
- Various Tyre Upgrades
- Extension Sides
- High Speed Running Gear
- Air Brakes c/w Load Sensing

## Farm Dump Trailer Suspension Options :-



**Sprung Axles** Beam axles with heavy duty multi-leaf semi-elliptical sprung suspension for a smoother ride and reduced tyre wear



**Bogie Axles** Stub axles with 'rocking beam' suspension complete with 60mm diameter chrome pivot pin and bronze bushes

## Farm Dump Trailer Optional Extras :-



**Sprung Drawbar**



**Tyre Upgrades**  
(many options available including Flotation tyres)



**Contractor Hydraulic Tailboard**

**Extension Sides**

**Mudguards**

**High Speed Running Gear**

## 6½ Tonne, 7 Tonne & 8 Tonne Farm Dump Trailers

	6½ Tonne Farm Dump (single axle)		7 Tonne Farm Dump (tandem axle)		8 Tonne Farm Dump (tandem axle)	
Body length	3660mm	12'	3660mm	12'	4300mm	14'
Body width (av 6" taper)	2210mm	7' 3"	2210mm	7' 3"	2210mm	7' 3"
Body height	1070mm	3' 6"	1117mm	3' 8"	1117mm	3' 8"
Floor thickness	5mm		5mm		5mm	
Side thickness	3mm		3mm		3mm	
Chassis	180 x 75 PFC		180 x 75 PFC		250 x 150 RHS	
Axle size	80mm 6 stud (single)		70mm 6 stud (tandem)		70mm 6 stud (tandem)	
Brake size	300 x 60mm		300 x 60mm		300 x 60mm	
Wheel track	2000mm	6' 6¾"	2000mm	6' 6¾"	2000mm	6' 6¾"
Tyre size	12.5/80 x 15.3 14 ply		11.5/80 x 15.3 10 ply		12.5/80 x 15.3 14 ply	
Cubic capacity	m <sup>3</sup>	ft <sup>3</sup>	m <sup>3</sup>	ft <sup>3</sup>	m <sup>3</sup>	ft <sup>3</sup>
o/a length	5080mm	16' 6"	5080mm	16' 8"	5800mm	19'
o/a width	2440mm	8'	2440mm	8'	2440mm	8'
o/a height	2070mm	6' 10"	2210mm	7' 3"	2290mm	7' 6"
Max tipped height	4810mm	15' 10"	4990mm	16' 5"	5900mm	19' 4"
Unladen weight	1.5 Tonne approx		1.8 Tonne approx		2.1 Tonne approx	

## 10 Tonne, 12 Tonne & 14 Tonne Farm Dump Trailers

	10 Tonne Farm Dump (tandem axle)		12 Tonne Farm Dump (tandem axle)		14 Tonne Farm Dump (tandem axle)	
Body length	4710mm	15' 6"	5480mm	18'	6080mm	20'
Body width	2210mm	7' 3"	2210mm	7' 3"	2210mm	7' 3"
Body height	1270mm	4' 2"	1270mm	4' 2"	1270mm	4' 2"
Floor thickness	5mm		5mm		5mm	
Side thickness	3mm		3mm		3mm	
Chassis	250 x 150 RHS		250 x 150 RHS		250 x 150 RHS	
Axle size (tandem)	80mm 8 stud		90mm 10 stud commercial		90mm 10 stud commercial	
Brake size	350 x 60mm		406 x 120mm		406 x 120mm	
Wheel track	2000mm	6' 6¾"	2000mm	6' 6¾"	2000mm	6' 6¾"
Tyre size	385/65R22.5 'super single'		385/65R22.5 'super single'		385/65R22.5 'super single'	
Cubic capacity	12.8m <sup>3</sup>	450ft <sup>3</sup>	15.0m <sup>3</sup>	530ft <sup>3</sup>	17.0m <sup>3</sup>	590ft <sup>3</sup>
o/a length	6250mm	20' 6"	6590mm	22' 10"	7190mm	24' 10"
o/a width	2440mm	8'	2440mm	8'	2440mm	8'
o/a height	2465mm	8' 1"	2500mm	8' 2"	2550mm	8' 4"
Max tipped height	6325mm	20' 6"	6980mm	22' 11"	7430mm	24' 5"
Unladen weight	3.1 Tonne approx		3.6 Tonne approx		4.0 Tonne approx	