

AW TRAILERS

Industrial Dump Trailers

The AW range of Industrial Dump Trailers have a very heavy duty construction and are designed to carry materials such as stone, rubble, soil and earth.



The AW Industrial Dump Trailers have a scow-ended body built from 6mm (¼") thick plate supported by wide side channels.

They have strong wide parallel chassis built from RHS or PFC and high specification running gear.

The tandem axle models can be fitted with either sprung or bogie suspension. There are 6½ Tonne, 7 Tonne, 8 Tonne, 10 Tonne, 12 Tonne and 14 Tonne models available.

There is also a 16 Tonne Industrial Dump Trailer available in our high spec *Ultima* range.



Standard features include :-

- Hydraulic tipping
- Hydraulic brakes
- LED full road lighting
- Commercial ratchet type parking brake
- Inspection steps
- Rope hooks
- Heavy duty heat treated hitch eye
- RHS box body top on models 8 Tonne & over
- Removable drawbar skid

Optional extras available include :-

- Sprung drawbar
- Manual tailboard
- Standard hydraulic tailboard
- Contractor hydraulic tailboard
- High speed running gear
- Air brakes with load sensing
- Extension sides
- Various tyre upgrades

AW Engineering (Hereford) Ltd.
Stoney Street
Madley
Hereford
HR2 9NQ

Tel : 01981 251558
Fax : 01981 251568

Web : www.awtrailers.co.uk
Email : sales@awtrailers.co.uk

	6.5 Tonne Ind Dump		7 Tonne Ind Dump		8 Tonne Ind Dump	
Body length (internal)	3630mm	11' 11"	3630mm	11' 11"	4210mm	13' 8"
Body width (internal) av 6" taper	2210mm	7' 3"	2210mm	7' 3"	2210mm	7' 3"
Body height	610mm	2'	610mm	2'	610mm	2'
Floor thickness	6mm		6mm		6mm	
Side thickness	6mm		6mm		6mm	
Cubic capacity	4.4m ³	155ft ³	4.4m ³	155ft ³	5.1m ³	180ft ³
Chassis	180 x 75 PFC		180 x 75 PFC		250 x 150 RHS	
Axle size	80mm 6 stud (single)		70mm 6 stud (tandem)		70mm 6 stud (tandem)	
Brake size	300 x 60mm		300 x 60mm		300 x 60mm	
Wheel track	2000mm	79"	2000mm	79"	2000mm	79"
Tyre size	12.5/80 x 15.3 14 ply		11.5/80 x 15.3 10 ply		12.5/80 x 15.3 14 ply	
O/a length	5050mm	16' 7"	5050mm	16' 7"	5740mm	18' 8"
O/a width	2440mm	8'	2440mm	8'	2440mm	8'
O/a height	1520mm	5'	1520mm	5'	1730mm	5' 8"
Max tipped height	4280mm	14' 1"	4400mm	14' 5"	4980mm	16' 4"
Unladen weight	1.6 Tonne approx		1.9 Tonne approx		2.2 Tonne approx	

	10 Tonne Ind Dump		12 Tonne Ind Dump		14 Tonne Ind Dump	
Body length (internal)	4210mm	13' 8"	4490mm	14' 9"	4720mm	15' 6"
Body width (internal) av 6" taper	2210mm	7' 3"	2210mm	7' 3"	2210mm	7' 3"
Body height	730mm	2' 5"	730mm	2' 5"	915mm	3'
Floor thickness	6mm		6mm		6mm	
Side thickness	6mm		6mm		6mm	
Cubic capacity	5.6m ³	200ft ³	6.1m ³	215ft ³	9.2m ³	320ft ³
Chassis	250 x 150 RHS		250 x 150 RHS		250 x 150 RHS	
Axle size (tandem)	80mm 8 stud		127mm 10 stud commercial	127mm 10 stud commercial		
Brake size	350 x 60mm		406 x 120mm		406 x 120mm	
Wheel track	2000mm	79"	2000mm	79"	2000mm	79"
Tyre size	385/65R22.5 'super single'		385/65R22.5 'super single'		385/65R22.5 'super single'	
O/a length	5740mm	18' 8"	6060mm	19' 10"	6150mm	20' 2"
O/a width	2440mm	8'	2440mm	8'	2440mm	8'
O/a height	1980mm	6' 6"	1980mm	6' 6"	2210mm	7' 3"
Max tipped height	5160mm	16' 11"	5790mm	19'	5850mm	19' 2"
Unladen weight	2.6 Tonne approx		3.0 Tonne approx		4.1 Tonne approx	

	16T <i>Ultima</i> Ind Dump		18T <i>Ultimaxtra</i> Ind Dump	
Body length (internal)	4720mm	15' 6"	4720mm	15' 6"
Body width (internal)	2275mm	7' 6"	2275mm	7' 6"
Body height	915mm	3'	915mm	3'
Floor thickness	8mm		6mm Hardox wear plate	
Side thickness	6mm		5mm Hardox wear plate	
Cubic capacity	9.8m ³	349ft ³	9.8m ³	349ft ³
Chassis	250 x 150 RHS		250 x 150 RHS	
Axle size (tandem)	127mm 10 stud commercial		127mm 10 stud commercial	
Brake size	420 x 180mm		420 x 180mm	
Wheel track	2000mm	79"	2000mm	79"
Tyre size	445/65R22.5		445/65R22.5	
O/a length	6150mm	20' 2"	6150mm	20' 2"
O/a width	2455mm	8' 1"	2455mm	8' 1"
O/a height	2345mm	7' 8"	2345mm	7' 8"
Max tipped height	5950mm	19' 6"	5950mm	19' 6"
Unladen weight	4.5 Tonne approx		4.1 Tonne approx	



QUALITY

DURABILITY

RELIABILITY

AW Engineering (Hereford) Ltd.
Stoney Street,
Madley,
Hereford,
HR2 9NQ

Tel : 01981 251558
Fax : 01981 251568

www.awtrailers.co.uk
sales@awtrailers.co.uk