

Stone & Rubble Trailers



6½ Tonne Stone & Rubble Trailer



7 Tonne Stone & Rubble Trailer



8 Tonne Stone & Rubble Trailer



8 Tonne Stone & Rubble Trailer with optional 'Barn Doors' and Aluminium Loading Ramps



10 Tonne Stone & Rubble Trailer

The AW Stone & Rubble Trailers are designed to carry stone, earth and rubble. They have a tapered body with 6mm (¼") thick floor and sides supported by wide side channels. They have strong wide parallel chassis built from RHS or PFC and high specification running gear. The tandem axle models can be fitted with either sprung or bogie suspension. There are 6½ Tonne, 7 Tonne, 8 Tonne, 10 Tonne, and 12 Tonne models available. There is also a 14 Tonne Stone & Rubble Trailer available in our high spec *Ultima* range.

Standard Stone & Rubble Trailer Features :-

- Hydraulic Tipping
- Hydraulic Brakes
- Commercial Ratchet type Park Brake
- Full Road Lighting
- Top Hinged Tailboard c/w Latching Bar
- Inspection Steps
- Rope Hooks
- Removable Drawbar Skid
- RHS Box Top on 10 Tonne model & above

Optional Extras Available include :-

- Sprung Drawbar
- Barn Doors
- Aluminium Loading Ramps
- Standard Hydraulic Tailboard
- Contractor Hydraulic Tailboard
- Grain Chute
- Extension Sides
- Various Tyre Upgrades
- High Speed Running Gear
- Air Brakes c/w Load Sensing

Stone & Rubble Trailer Suspension Options :-



Sprung Axles Beam axles with heavy duty multi-leaf semi-elliptical sprung suspension for a smoother ride and reduced tyre wear



Bogie Axles Stub axles with 'rocking beam' suspension complete with 60mm diameter chrome pivot pin and bronze bushes

Stone & Rubble Trailer Optional Extras :-



Sprung Drawbar



Tyre Upgrades
(many options available including Flotation tyres)



Barn Doors
Aluminium Loading Ramps

6½ Tonne & 7 Tonne Stone & Rubble Trailers

	6½ Tonne Stone & Rubble (single axle)		7 Tonne Stone & Rubble (tandem axle)	
Body length	3660mm	12'	3660mm	12'
Body width (av 6" taper)	2210mm	7' 3"	2210mm	7' 3"
Body height	610mm	2'	610mm	2'
Floor thickness	6mm		6mm	
Side thickness	6mm		6mm	
Chassis	180 x 75 PFC		180 x 75 PFC	
Axle size	80mm 6 stud (single)		70mm 6 stud (tandem)	
Brake size	300 x 60mm		300 x 60mm	
Wheel track	2000mm	6' 6¾"	2000mm	6' 6¾"
Tyre size	12.5/80 x 15.3 14 ply		11.5/80 x 15.3 10 ply	
Cubic capacity	4.9m ³	174ft ³	4.9m ³	174ft ³
o/a length	5080mm	16' 8"	5080mm	16' 8"
o/a width	2440mm	8'	2440mm	8'
o/a height	1560mm	5' 2"	1635mm	5' 5"
Max tipped height	3890mm	12' 9"	3970mm	13' 1"
Unladen weight	1.5 Tonne approx		1.8 Tonne approx	

8 Tonne, 10 Tonne & 12 Tonne Stone & Rubble Trailers

	8 Tonne Stone & Rubble (tandem axle)		10 Tonne Stone & Rubble (tandem axle)		12 Tonne Stone & Rubble (tandem axle)	
Body length	4300mm	14'	4710mm	15' 6"	5505mm	18'
Body width (av 6" taper)	2210mm	7' 3"	2210mm	7' 3"	2210mm	7' 3"
Body height	610mm	2'	610mm	2'	610mm	2'
Floor thickness	6mm		6mm		6mm	
Side thickness	6mm		6mm		6mm	
Chassis	250 x 150 RHS		250 x 150 RHS		250 x 150 RHS	
Axle size (tandem)	70mm 6 stud		80mm 8 stud		90mm 10 stud commercial	
Brake size	300 x 60mm		350 x 60mm		406 x 120mm	
Wheel track	2000mm	6' 6¾"	2000mm	6' 6¾"	2000mm	6' 6¾"
Tyre size	12.5/80 x 15.3 14 ply		385/65R22.5 'super single'		385/65R22.5 'super single'	
Cubic capacity	5.8m ³	203ft ³	6.35m ³	225ft ³	8.2m ³	290ft ³
o/a length	5800mm	19'	6250mm	20' 6"	7045mm	23'
o/a width	2440mm	8'	2440mm	8'	2440mm	8'
o/a height	1780mm	5' 10"	1805mm	5' 11"	1805mm	5' 11"
Max tipped height	4620mm	15' 2"	5050mm	16' 7"	5620mm	18' 6"
Unladen weight	2.1 Tonne approx		3.0 Tonne approx		3.6 Tonne approx	